

CTF1013 ToolFace Tooling Adhesive Sheet

COMPOTOOL PTFE Coated Glass Fabric Sheet is using glass cloth base material impregnated with PTFE (polytetrafluoroethylene) dispersion and then sintered. Single surface treated and coated with a high-temperature, silicone pressure-sensitive adhesive. Compotool ToolFace is supplied as rolls. Yellow textured PVC release liner is applied to the adhesive surface for ease of application.

Key Features:

- Good holding properties and dimensional stability at elevated temperatures.
- Superior mould-releasing and sliding properties.
- The non-adhesive side exhibits excellent characteristics of PTFE such as electrical properties, resistance to heat, weather and water.

Technical Information:

ToolFace CTF1013	
Thickness	0.13mm (.005 Inches)
Width	1000mm (39.37 Inches)
Weight	195±5 g/m ² (.040 Lbs/ft ²)
Temperature Resistance	-70°C to +260°C (-94°F to +500°F)

Storage:

COMPOTOOL ToolFace must be stored in a dry location. Handle with care to avoid damage.

Supply

COMPOTOOL ToolFace CTF-1013	1 Meter wide rolls cut to desired length up to 50m.
-----------------------------	---

Health and Safety

FOR INDUSTRIAL OR PROFESSIONAL USE ONLY.

DO NOT HANDLE UNTIL PRECAUTIONS ON THE SAFETY DATA SHEET HAS BEEN CAREFULLY READ AND UNDERSTOOD.

FOR ADDITIONAL ENVIROMENTAL, HEALTH AND SAFTY INFORMATION REFER TO SAFETY DATA SHEET.

BY ACCEPTING THE GOODS SUPPLIED BY COMPOTOOL SELLER AND BUYER AGREE TO THE FOLLOWING LIMITED WARRANTY AND REMEDIES LIMITATIONS:

COMPOTOOL warrants that goods sold will be merchantable. If goods are defective, Buyer may return them at Buyer's cost to COMPOTOOL within 12 months of purchase for a full refund of the purchase price. Other than this limited warranty, there are no express or implied warranties. There is no warranty as to fitness for a particular use. COMPOTOOL recommends that The Buyer shall take all recommended safety precautions while working with the goods. COMPOTOOL and Buyer agree that other than return of the purchase price COMPOTOOL will not be liable for any damages, consequential damages or incidental damages. When handling this product prolonged skin contact may lead to skin irritation and airborne dust can be released. It is recommended that suitable gloves, respiratory and eye protection equipment are used when handling. When sanding and machining use appropriate dust extraction and work in a well-ventilated area.

All information contained in this data sheet is given in good faith and based on tests believed to be reliable. COMOPTOOL Ltd. makes no warranty of fitness for a particular use. It is the responsibility of the user to determine the suitability of the products for their intended use and to assume all risk and liability in connection with their use. This Information will be periodically reviewed and may be subject to modification.